

MATERIAL SAFETY DATA SHEET

HMIS HAZARDOUS MATERIALS

(Prepared According to 29 CFR 1910.1200)

A = Safety Glasses
B = A + Gloves
C = B + Apron
D = C + Face Shield
E = B + Dust Mask

F = C + Dust Mask
G = B + Respirator
H = F + Goggles
I = B + Respirator
X = Ask Supervisor

4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant

IDENTIFICATION SYSTEM

Health... 1
Flammability... 0
Reactivity... 0
Protection... A

SECTION I - PRODUCT IDENTIFICATION

Product Code: 310 Supersedes date: date: April 18, 1997 Section(s) changed: I, II, VII, VIII, X Effective Date: April 25, 2003

PRODUCT NAME: ACRY-SEAL
GENERIC NAME: Resilient Tile Undercoater
DISTRIBUTORS NAME:

CHEMICAL FAMILY: Acrylic Sealer
FORMULA: Proprietary Mixture
DISTRIBUTORS ADDRESS:

INFORMATION PHONE NUMBER: 314-771-6600

EMERGENCY PHONE NUMBER IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE OR ACCIDENT: CHEMTREC 800-424-9300

PROPER SHIPPING DESCRIPTION: Compounds, polishing liquid

LABEL: None

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS No.	Wt%	OSHA PEL	ACGIH TLV	OTHER
2-(2-ethoxyethoxy)Ethanol	111-90-0	<5	NE	NE	
Dipropylene glycol monomethylether	34590-94-8	<5	100 mg/m ³	100 ppm	

The information & recommendations set forth herein are presented in good faith & believed to be current & reliable. The manufacturer makes no representation as to the completeness or accuracy thereof & supplies information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will the manufacturer be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which it refers.

SECTION III - PHYSICAL/CHEMICAL DATA

Boiling Point (°F): 212
Vapor Pressure (mm Hg): 17
Vapor Density (Air=1): 0.62
Evaporation Rate: (Water=1): GT 1.0
Solubility in Water: Complete Dispersible
Physical Description: Opaque White Thin Liquid
Characteristic Odor

Specific Gravity: 1.032
Lbs/Gal Density: 8.6
pH Concentrate: 10.0
pH Use Dilution: 10.0

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (Method Used): None LIMITS: LEL: NA UEL: NA
EXTINGUISHING MEDIA: Water spray or fog, foam, dry chemical, carbon dioxide, alcohol foam, if product is involved.
SPECIAL FIRE FIGHTING PROCEDURES: Avoid exposure to fumes or vapors. Wear self-contained positive pressurized breathing apparatus MSHA/NIOSH Approved or equivalent to maintain TLV.
UNUSUAL FIRE & EXPLOSION HAZARD: Use water spray to cool adjacent fire exposed containers. Product will not burn but may splatter if temperature exceeds boiling point.

SECTION V - REACTIVITY DATA

Stability: Stable; protect from freezing. Store below 115° F.
Hazardous Polymerization: Will not occur.
Incompatibility (Materials to Avoid): Strong oxidizing, reducing agents; acids; alkalies; cationics.
Hazardous Decomposition Products: If burned, Carbon Dioxide, Ammonia, Nitrous Oxides.

SECTION VI - STORAGE & HANDLING INFORMATION

KEEP OUT OF REACH OF CHILDREN. CAUTION.
Store upright in original closed container.
Other Precautions: Do not get in eyes, on skin or on clothing. Remove & wash contaminated clothing before reuse.

SECTION VII - HEALTH HAZARDS AND FIRST AID

Carcinogenicity:	NTP?	IARC Monographs?	OSHA REGULATED?
NE	NE	NE	NO

EFFECTS OF OVEREXPOSURE:
SKIN: Irritation
EYES: Irritation
INHALATION: Irritation

EMERGENCY FIRST AID PROCEDURES:
SKIN: Wash with soap & water. See physician if irritation persists.
EYES: Flush with flowing water for 15 minutes & see physician.
INHALATION: Remove to fresh air.
INGESTION: Give a teaspoonful of milk of magnesia, followed by milk or water to dilute material; DO NOT induce vomiting. Avoid alcohol. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: (Specify type) Normal room ventilation.
VENTILATION: Avoid breathing vapor or spray.
PROTECTIVE GLOVES: N/A.
EYE PROTECTION: Safety glasses.
OTHER PROTECTIVE EQUIPMENT: N/A

SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Mop up & flush to sewer with plenty of water. Floors may be slippery. Use care to avoid falls.
WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State & Local regulations.

SECTION X - ADDITIONAL FEDERAL REGULATIONS

SARA TITLE III (EPCRA) NOTIFICATION: GLYCOL ETHERS
COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT (CERCLA): GLYCOL ETHERS
For more information, consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68.

NE - Not Established NA - Not Applicable GT - Greater Than

Manufactured by: Intercon Chemical Company 1100 Central Industrial Drive, St. Louis, MO 63110