

HIGH SOLIDS THERMOPLASTIC FLOOR FINISH

interplex 25™



Description

This state-of-the-art thermoplastic finish combines the ultimate in toughness with a crystal clear “wet look” gloss in a labor saving, high solids formula. Excellent leveling that dries to a tough, yet flexible, film. Easily maintained to an extended service life with compatible cleaners and buffing compounds. The low odor level of this product makes it more pleasant to use than traditional type finishes.

Features...Benefits

- High Solids FormulaLabor Saving
- Extremely Tough FilmImproved Performance
- Excellent LevelingEasy to Use
- Dries BrightLabor Saving
- Multi-Speed BuffableEasy to Use

Directions For Use

Apply to cleaned or stripped floor in a uniform coat using a clean mop or applicator. Allow to dry and recoat. Apply a minimum of 3 coats to establish a sound base coating. Maintain with cleaners as recommended. Periodic restoring is optional. Traffic aisles should be thoroughly scrubbed clean before recoating as part of a regular maintenance program. Follow the Floor Care Procedures as listed in the INTERCON FLOOR CARE MANUAL.

Product Properties

COLOR (LIQUID): Milky White
COLOR (DRIED): Clear Colorless
ODOR: Mild
pH: 8-9
FLASH POINT: None
SPECIFIC GRAVITY: 1.032
NON VOLATILE SOLIDS: 25.0%
LEVELING: Excellent
COVERAGE: AVG. 2000 sq. ft./gal.

Safety Information

KEEP OUT OF REACH OF CHILDREN
CAUTION: DO NOT TAKE INTERNALLY. Avoid contact with skin, eyes and clothing. IF ON SKIN, wash with soap and water immediately. Seek medical attention if irritation persists. IF IN EYES, flush with flowing water for 15 minutes and seek medical attention. IF INGESTED, drink milk or water to dilute material. DO NOT induce vomiting. Call a physician or poison control center immediately.

MSDS available at www.interconchemical.com

REFER TO PRODUCT LABEL AND MSDS
FOR ADDITIONAL INFORMATION

060314-311

© INTERCON 2006