

PROPANE BURNISHABLE FLOOR FINISH

interplex pro 22™



1100 Central Industrial Drive
St. Louis, Mo 63110
1-800-325-9218
314-771-6600

E-Mail: info@interconchemical.com
www.interconchemical.com

Product Properties

COLOR (LIQUID): Opaque White
COLOR (DRIED): Clear Colorless
ODOR: Mild
pH: 8-9
FLASH POINT: None
SPECIFIC GRAVITY: 1.012
NON VOLATILE SOLIDS: 22%
LEVELING: Excellent
COVERAGE: AVG. 2000 sq. ft./gal.

Description

This state-of-the-art propane burnishable finish combines the ultimate in toughness with a crystal clear “wet look” gloss in a labor saving, high solids formula. Excellent leveling that dries to a tough, yet flexible, film. Easily maintained to an extended service life with compatible cleaners and buffing compounds. The low odor level of this product makes it more pleasant to use than traditional type finishes.

Features...Benefits

- Extremely Tough FilmImproved Performance
- Provides Extended Service LifeLabor Saving
- Excellent LevelingEasy to Use
- Dries BrightLabor Saving
- Multi-Speed BuffableEasy to Use

Directions For Use

Apply to cleaned or stripped floor in a uniform coat using a clean mop or applicator. Allow to dry and recoat. Apply a minimum of 3 coats to establish a sound base coating. Maintain with cleaners as recommended. Periodic restoring is optional. Traffic aisles should be thoroughly scrubbed clean before recoating as part of a regular maintenance program. Follow the Floor Care Procedures as listed in the INTERCON FLOOR CARE MANUAL.

Safety Information

KEEP OUT OF REACH OF CHILDREN
CAUTION: DO NOT TAKE INTERNALLY. Avoid contact with skin, eyes and clothing. IF ON SKIN, wash with soap and water immediately. Seek medical attention if irritation persists. IF IN EYES, flush with flowing water for 15 minutes and seek medical attention. IF INGESTED, drink milk or water to dilute material. DO NOT induce vomiting. Call a physician or poison control center immediately.

070122-317

© INTERCON 2007

REFER TO PRODUCT LABEL AND MSDS
FOR ADDITIONAL INFORMATION