

URETHANE FORTIFIED METAL INTERLOCK FINISH

interthane™



Description

This premium urethane/acrylic floor finish and seal offers state of the art performance and features distinct advantages in floor recoatability, fast drying and durability. Use of this product extends finish service life dramatically and can provide significant savings in the labor segment of the floor care budget.

Features...Benefits

- High DurabilityLonger Service Life
- Slip ResistantReduces Risk
- Self SealingLabor Saving
- Excellent LevelingEasy to Use
- Dries BrightLabor Saving

Directions For Use

Apply to clean, stripped floor in a uniform thin coat using a clean mop or applicator. Allow to dry (20 - 30 minutes) and recoat. Apply a minimum of 3 coats of finish to establish a sound base coating. Maintain using cleaners and buffing compounds as recommended.

Product Properties

COLOR (LIQUID): Milky White
COLOR (DRIED): Clear Colorless
ODOR: Mild
pH: 9.0
FLASH POINT: None
SPECIFIC GRAVITY: 1.025
NON VOLATILE SOLIDS: 18.0%
LEVELING: Excellent
COVERAGE: AVG. 2000 sq. ft./gal.

Safety Information

KEEP OUT OF REACH OF CHILDREN
CAUTION: Avoid contact with eyes and skin. In case of contact, rinse thoroughly. Do not take internally.