

FLOATING LIFT STATION CLEANER

lift-solv™



Description

This floating, liquid sewer solvent dissolves and emulsifies the greasy waste that forms on the walls and collects in the pumps of lift stations as the platform level rises and falls. It contains odor neutralizing agents to inhibit the escape of objectionable odors. Regular use of this product eliminates the difficult and obnoxious job of manual cleaning of lift stations.

Features...Benefits

- Ready to Use Convenient
- Reduces Lift Station Odor Improved Public Perceptions
- Floats on Platform Level Labor Saving
- Speeds Settling Rate . . . Improves Plant Efficiency
- Versatile Ease of Use

Directions For Use

LIFT STATIONS: Add directly to lift station. A 2-4 inch layer on the top of lift station waste water will keep the unit grease free and provides continuous cleaning action. Check level monthly to determine if more solvent is needed.

WET WELLS: Drip this product directly into the well or treat as above.

Use as a solvent on sides of primary tanks, in sewer lines and throughout your plant and system.

Product Properties

COLOR: Clear, Red
ODOR: Solvent
VISCOSITY: 10 cps
SPECIFIC GRAVITY: 0.819
FLASH POINT: 106°F
SOLUBILITY IN WATER: Not Soluble

Safety Information

KEEP OUT OF REACH OF CHILDREN
WARNING: Combustible. Keep away from heat, sparks and open flame. Harmful if swallowed. Do not get in eyes, on skin or clothing. In case of contact with eyes, flush with flowing water for 15 minutes and seek medical attention. In case of contact with skin, wash with soap and water. Seek medical attention if irritation persists. If swallowed, seek medical attention immediately.