

VERY AGGRESSIVE RINSE FREE SPEED STRIPPER

strip 'n go plus™



Description

This time and labor saving stripper works by breaking the molecular "film forming" bond of floor finishes and waxes. It "re-emulsifies" all but the heaviest finish buildups with or without scrubbing. This allows the stripper to be applied by mop and picked up by mop and bucket or wet vac. Any remaining solution evaporates completely - eliminating the need to rinse before recoating. Unlike ordinary strippers, no alkali film is left behind to prevent bonding of new finish to the floor.

Features...Benefits

- ConcentratedEconomical
- Fast ActingLabor Saving
- Completely Rinse FreeLabor Saving
- Removes Many Types of FinishEase of Use
- Low OdorPleasant to Use

Directions For Use

Dilute this product with hot water at 1:4 - 1:10. Apply diluted stripper generously to floor with a clean mop and allow to stand on floor to attack and "whiten" finish. Scrub with a stripping (black) pad. Pick up solution thoroughly with a mop or wet vac. Allow floor to dry completely then dust mop with a clean, dry mop before refinishing.

Safety Information

KEEP OUT OF REACH OF CHILDREN

DANGER: Severe eye and skin irritant. Vapors harmful. Avoid contact with skin and eyes. Do not breathe vapors. Harmful if swallowed. When handling concentrated product, wear eye protection and rubber gloves. Remove contaminated clothing immediately. **IN CASE OF CONTACT WITH EYES:** Immediately flush with water for 15 minutes. If irritation persists, get medical attention. **IF SWALLOWED:** Drink a large quantity of water or milk. Seek medical attention immediately. **IN CASE OF CONTACT WITH SKIN:** Flush with water. If irritation persists, get medical attention. **INHALATION:** Get to fresh air.



1100 Central Industrial Drive
St. Louis, Mo 63110
1-800-325-9218
314-771-6600

E-Mail: info@interconchemical.com
www.interconchemical.com

Product Properties

COLOR: Clear Colorless
ODOR: Sassafras
VISCOSITY: 10 cps
pH: 13.0
SPECIFIC GRAVITY: 1.05
FLASH POINT: None
FOAMING: Low
SOLUBILITY IN WATER: Complete

060314-745

© INTERCON 2006

REFER TO PRODUCT LABEL AND MSDS
FOR ADDITIONAL INFORMATION