

CONCENTRATED FLOOR FINISH STRIPPER

interstrip™



1100 Central Industrial Drive
St. Louis, Mo 63110
1-800-325-9218
314-771-6600
E-Mail: info@interconchemical.com
www.interconchemical.com

Product Properties

COLOR: Clear Green
ODOR: Pleasant
VISCOSITY: 50 cps
pH: 13
FLASH POINT: None
FOAMING: Moderate
SOLUBILITY IN WATER: Complete
RINSABILITY: Complete

Description

This concentrated machine stripper removes all types of metal interlock and thermoplastic high speed finishes. It works by “breaking the bond” between polymer molecules that are the base of modern finishes, creating an emulsion that is easily picked up by mopping or wet vac. This stripper is formulated to help maintain quality flooring and improve recoat performance.

Features...Benefits

- ConcentratedEconomical
- VersatileEase of Use
- Fast ActingLabor Saving
- Non-FumingPleasant to Use

Directions For Use

- 1) Dilute stripper with water. NOTE: Higher concentrations will increase stripping speed and reduce job time.
- 2) Apply diluted stripper generously to the floor, with a clean mop, to thoroughly wet all surfaces. Allow solution to stand and soak on floor at least 5 minutes to chemically attack, “whiten” and lift finish, wax coating and soil. Do not allow floor to dry.
- 3) Scrub with a stripping pad to break up and solubilize floor coating and dirt.
- 4) Pick up solution thoroughly with a mop, squeegee, or wet vacuum and rinse thoroughly with clear water. Neutralizer added to rinse water and complete rinsing and pick up of stripper solution will insure seal and finish recoat beauty and durability.

Safety Information

KEEP OUT OF REACH OF CHILDREN
CAUTION: May cause irritation to skin or eyes. In case of contact with eyes, flush with plenty of water. If irritation persists, see a physician. In case of contact with skin, flush with plenty of water.