

# inter-seal

## WATER BASED MODIFIED ACRYLIC POLYMER SEAL

### Product Properties

COLOR (LIQUID): Milky White  
ODOR (DRIED): Clear Colorless  
ODOR: Mild  
pH: 8-9  
FLASH POINT: None  
SPECIFIC GRAVITY: 1.03  
NON VOLATILE SOLIDS: 18.0%  
LEVELING: Excellent  
COVERAGE: AVG. 2000 sq.ft./gal.

### Description

This product is an extremely durable acrylic polymer seal that offers state-of-the-art performance when used for concrete, stone, marble, ceramic, tile and other non-resilient flooring. It gives equally superb results on old, new, rough, porous or smooth substrates. This sealer has a non-solvent base, is safe and easy to use, easy to clean up and has a faster drying time than many solvent-type products. Highly recommended for all surfaces appropriate for water based maintenance. Provides excellent gloss, low color and high clarity. Will not strip using ordinary floor strippers.

### Features...Benefits

Non-Solvent .....Safer to Use  
Slip Resistant ..... Reduces Risk  
Extremely Durable ..... Longer Service Life  
Easy Clean Up ..... Ease of Use  
Will Not Strip with Ordinary Strippers ... Longer Service Life

### Directions

Thoroughly sweep and clean floor with a suitable detergent and rinse before application to prevent embalming dirt and stains and to insure proper coating and wear properties. No etching or neutralizing is necessary. Apply seal with a clean applicator, roller, quality string mop or sprayer generously, without puddling, to insure adequate protection and easy maintenance. For best results, apply two to three coats, allowing seal to dry between coats (about 30 minutes depending on ventilation, humidity, temperature and porosity). Top coats of wax or finish may be applied if desired. Allow an overnight cure before resuming heavy traffic. NOTE: This seal is very difficult to remove when dried. Do not apply or splash onto unintended areas.

### Safety Information

KEEP OUT OF REACH OF CHILDREN  
CAUTION

Avoid contact with eyes and skin. In case of contact, rinse thoroughly. Do not take internally.

1100 Central Industrial Dr.  
St. Louis, Missouri, 63110

toll free: 800 325 9218  
main: 314 771 6600  
fax: 314 771 6608

[www.interconchemical.com](http://www.interconchemical.com)



161115-0364  
© INTERCON 2016

REFER TO PRODUCT LABEL AND SDS  
FOR ADDITIONAL INFORMATION